

## SCHEDULE WORK

**Subject:- Supply, Installation, Testing & Commissioning of CCTV surveillance in the premises of Red Cross Society, National Headquarters at 1, Red Cross Road, New Delhi:**

<b>SITC of CCTV Surveillance System ( 4MP Camera)</b>						
<b>S.No</b>	<b>Item Description</b>	<b>Make/Model</b>	<b>Qty</b>	<b>Unit</b>	<b>Unit Price with Tax</b>	<b>Total Amount</b>
1	4 MP Full HD IR Bullet Camera - 30Mtr. 1/3" 4MP PS CMOS Image Sensor 20fps@4MP(2688×1520) and 25/30fps@3MP(2304×1296) H.265+ / H.265 dual-stream encoding DWDR, Day/Night(ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC 2.8 mm fixed lens (3.6 mm optional) IR Range of 30 Mtrs, IP67, PoE Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro, vOptimus Pro		6	Nos		
2	4MP Full HD WDR IR Network Bullet Camera - 40Mtr. 1/3" 4Megapixel PS CMOS Image Sensor 25/30fps@4MP(2688×1520) H.265 and H.264 triple-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens (6mm optional) IR Range of 40 Mtrs, IP67, Micro SD Card, ePoE Mobile Software: iCMOB, gCMOB CMS Software: KVMS Pro, vOptimus Pro		3	Nos		

3	<p>16 Ch. H.265 Network Video Recorder Support up to 1ch@8MP/4ch@1080P decoding H.265/H.264 dual codec decoding Up to 8MP resolution preview and playback Max 160Mbps incoming bandwidth Support 2 SATA HDDs up to 12TB, 2 USB ports(2.0) HDMI / VGA simultaneous video output Support Multi-brand network cameras ONVIF Version 2.4 conformance Mobile Software: iCMOB, gCMOB CMS Software: KVMS, KVMS Pro</p>		1	Nos		
4	Hard Disc 6-TB		2	Nos		
5	<p>8-Port Fast Ethernet Switch with 8 PoE 8, 10/100Mbps; RJ45 ports; Max. 30W Output of Single PoE Port Support IEEE802.3/802.3u/802.3ab/802.3z/802.3x 2, 10/100Mbps; Transmission Distance: 0-100m</p>		2	Nos		
6	<p>16 Ports PoE Switch Provide 16x 100Mbps downlink PoE Ethernet ports, 2x gigabit uplink Ethernet ports and 1x gigabit Fiber port Downlink Ethernet ports support PoE Plus , each port supports max. 30W output Support power consumption indication( LED indicates power output status) Accord with IEEE802.3 , IEEE802.3u , IEEE802.3ab , IEEE802.3 af/at standard 4K MAC address,2. 75Mb cache</p>		1	Nos		
7	6 U Rack		1	Nos		
8	43" LED TV		1	Nos		
9	CAT 6 cable		1500	Meter		
10	HDMI Cable 10 Mtr		1	Nos		

11	RJ 45 connectors		40	Nos		
12	PVC Conduit Pipe 25 mm		600	Meter		
13	Other Accessories for installation		1	LS		
	<b>TOTAL</b>					

\*\*\*\*\*End of Document\*\*\*\*\*

(N. K. Singh)

Deputy Secretary